

- MATERIALS TO BE SUPPLIED BY EVERIDGE: 1 EA 2-PC STAINLESS STEEL CHASE WITH SMRT-100 TFT MOUNTED AND WIRE STUBBED OUT

- 18 EA #10 X ₹* STANLESS STEEL PAN HEAD SCREWS
 16 EA #10 X ₹* STANLESS STEEL PAN HEAD SCREWS
 15 MAGNETIC CONTACT SET (MAGNET AND RECEIVER) SURFACE MOUNT, WITH MOUNTING TAPE
 16 MAGNETIC CONTACT SET (MAGNET AND RECEIVER) SURFACE MOUNTACT WIRRING
 16 MAGNETIC SON THE MAGNETIC MOUNTED IN NON-MAIETALLIC ENCLOSURE
- 3 EA ‡* ID RUBBER GROMMETS (2 FOR INTERIOR CEILING, 1 FOR MAG CONTACT WIRE THRU CHASE)
 14 EA SMARTRITE PANIC BUTTON MOUNTED IN WEATHERPROOF JUNCTION BOX WITH NON-METALLIC IT CONDUIT AND 4-CONDUCTOR WIRE STUB
 16 AS MARTRITE LIGHT SWITCH MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 16 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 17 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 18 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH HON-METALLIC IT CONDUIT AND 3-CONDUCTOR WIRE STUB
 18 AMCH MOTION DETECTOR MOUNTED IN WEATHERPROOF JUNCTION BOX WITH MOUNTED IN WEATHERPROOF JUNCTION BOX WITH MOUNTED IN WEATHER WITH BOX WITH BOX

- FACTORY SCOPE OF WARK:

 1) SEE DRAWING SMRTOK-DEVDET FOR DEVICE SHOP ASSEMBLY DETAILS.

 2) MOUNT 16 64, 64 LYMNZED TH' ENCLOSURE BEHIND CUTOUT IN BOTTON PORTION OF STAINLESS STEEL CHASE.

 2) MOINE #22:24 4-CONDUCTOR CABLE TO REAR OF SMRTI-100 TH' DISPLAY

 3) WIRE #22:24 4-CONDUCTOR CABLE TO REAR OF SMRTI-100 TH' DISPLAY

 4) MSTALL SMRTI-100 TH' DISPLAY MITO ENCLOSURE MITH 25 FOOT 4-WIRE CABLE STUBBED OUT TOP THROUGH RUBBER GROMMET.

 5) ASSEMBLE WEATHERPROOF L'UNCTION BOXES FOR PAVIC AND LIGHT SWITCHES AND MOTION DETECTOR WITH CONDUIT AND WIRING BETWEEN AND STUBBED OUT TOP OF MD-1 AS INDICATED.
- 6) INSTALL AND WIRE DEVICES IN WEATHERPROOF JUNCTION BOXES AS INDICATED, WITH 25 FOOT 3 OR 4-WIRE CABLE STUBBED OUT TOP OF CONDUIT STUB.
- 7) INSTALL SMRT-100 POWER BASE INSIDE NON-METALLIC ENCLOSURE WITH BACK MOUNTING PLATE AND SCREW COVER.
 8) PACKAGE 2-PIECE STAINLESS STEEL CHASE WITH TFT ASSEMBLED, PANICLIGHT/MID-1 DEVICES ASSEMBLED WITH BOXES AND
- CONDUIT, TEMP/ %RH SENSOR, SURFACE MOUNTED MAGNETIC CONTACT SET, 3 GROMMETS , 16 EA STAINLESS STEEL SCREWS AND ONE SET OF FIELD INSTALLATION INSTRUCTIONS FOR SHIPMENT TO CUSTOMER.

	THIS DRAVING IS THE PROPERTY OF EVERIDGE. IT IS NOT TO BE ALTERED OR DISTRIBUTED TO OTHERS WITHOUT THE WRITTEN APPROVAL OF EVERIDGE.			
			NO.	
PEVERIDGE			DATE	
			BY	
				REVISIONS
27 MAR	INS	AMS	DESC	IONS
ജ	TALLEC	RTRITE	DESCRIPTION	
SWRT100RK-ELEV	NSTALLED ELEVATIONS	MARTRITE RETROFIT KIT		