



With flexible design for your unique setting, Everidge's ThermalRite® panel walk-in refrigeration units can be perfectly fitted for your cold storage space. Our durable modular options offer maximum efficiency, excellent construction and superior materials

Designed specifically to meet the needs of commercial and non-commercial foodservice institutions, ThermalRite panel walk-in coolers and freezers provide you with optimal cold storage for your kitchen, regardless of your particular foodservice application.

ThermalRite panel units allow you to design the perfect temperature controlled walk-in solution for your refrigerated space.

## Classifications & Approvals

All ThermalRite walk-in units are approved under numerous classifications, providing our customers with total peace of mind over perishable inventories:

- EISA-compliant
- NSF-certified
- U.L./Class 1-listed urethane foam insulation
- FM4880-approved (PN #713)
- USDA-approved materials
- UL/ULC electric
- UL Listed, Classified Building unit panels
- Meets the certification standards of multiple U.S. state and Canadian licensure and compliance codes

## Parts & Accessories

All ThermalRite walk-ins are available with a comprehensive range of accessories, allowing us to tailor your walk-in to suit the exact needs of your specific application and location.

Add the following to create the precise look and functionality required:

- LED lighting
- Alarm systems
- Digital thermometers
- Strip curtains
- Air curtains
- Door view ports
- Storage shelving
- Built-in wall supports
- Heavy duty floor plates
- Refrigeration systems
- Roof flashing systems (outdoor applications)
- Foamed-in-place electrical boxes

## Insulated Panels

- Non-HCFC insulation
- NSF-certified
- Thicknesses: 4", 5" or 6"
- Tongue-and-groove construction
- Air-tight seal

## Floor Panels

- Standard .050 smooth aluminum, Sanisteel or Acrylume
- Standard floor uniform load up to 1,000 lbs/sq ft
- Reinforced floor uniform load up to 5,000 lbs/sq ft
- Super floor uniform load up to 10,000 lbs/sq ft

## Structural Safety

- Easily constructed
- Metal-facing, foam-in-place bonding
- High-density foam rails
- Gasket application on all joints
- Cam lock panel fastening

## Finishes

- Internal and external Acrylume, as standard
- Optional: aluminum, stainless steel or antimicrobial Sanisteel
- White, black, almond or custom color paint
- Brick or stone effects available to complement the surrounding buildings

## Doors

- Flush mount self-closing swing operation doors
- High-quality, heavy-duty hardware and safety release
- Magnetic door gasket
- Pre-hung (up to 48")
- Heated door jamb and threshold (freezer models)

## Customization

- Door systems designed to accommodate space, access and egress
- Variable mounts, coils, and condensing units according to application needs
- Flooring, controls, and insulation levels tailored to fit space and application